MATERIAL SAFETY DATA SHEET OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

MATERIAL SA This MSDS complies with OSHA'S Hazard Commu			-	d OSHA Form	174	
IDENTITY AND MANUF					11/4	
	HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B					
	DOT Hazard Classification: ORM-D					
	Identity (trade name as used on label):					
Marietta, GA 30062	MISTY VANDALISM MARK REMOVER					
	MSDS Number: A00178 Revision- 13					
Information Calls: (770) 422-2071	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					
EMERGENCY RESPONSE NUMBER: 1(800)255-3924						
SECTION 1 - MATERIAL IDE	NTIFIC	ATION AND INFOR	MATION			
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **
ACETONE		67-64-1	No	1000	500 TWA	d
TOLUENE		108-88-3	Yes	200	50 (skin)	d
ISO BUTANE / PROPANE BLEND		75-28-5/74-98-6	No	800/1000	TWA 800/1000	d
METHYL ETHYL KETONE	78-93-3	Yes	200	200 TWA	d	
2-BUTOXYETHANOL (* glycol ether)	111-76-2	Yes*	25 skin	200 TWA	d	
		111-70-2	103	20 3011	20100	u
WARNING: This product contains a chemical or chemicals know the State of California to cause cancer, birth defects or other reproductive harm. SECTION 2 - PHYSICAL/C	HEMIC					
Boiling Point: N/A	Spe	cific Gravity (H2O=1):	Concent	rate Only = .	81	
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60		or Pressure (Non-Aero			erature): N/A	4
Vapor Density (Air = 1): N/E		poration Rate (= 1): N	N/E		
Solubility in Water: Partial	Wate	er Reactive: No				
Appearance and Odor: Clear liquid, aromatic solvent odor. SECTION 3 - FIRE AND			ТЛ			
		nition Temperature		ability Limits	in Air by %	in Volumo:
(aerosols): greater than 18" with flashback. Categorized:	auto igi	N/E		: N/E	% UEL	
EXTREMELY FLAMMABLE					70 OLL	
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparate		INGUISHER MEDIA:	oam, dry	chemical, carl	oon dioxide, w	vater.
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperature		a 130°E or the containe	r may run	ture		
SECTION 4 - REAC			r may rap			
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Acids and strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.						
Hazardous Decomposition Products: CO, CO2.				•		
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may c	ralieo k	neadache dizzinose	aenhuvi	a (death) ar	esthetic off	ects and
possible unconsciousness.	Jause		азрпул	a (ueatii), ai		
Eve Contact: Irritation	Skir	n Contact: Irritation				
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver						
abnormalities, kidney and/or lung damage. Lab animals have experienced anemia, liver, kidney, lung, blood damage to 2 butoxyethanol.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses			edical at	ention		
SECTION 6 - CONTROL A						
Respiratory Protection (specify type): If vapor concentration exceeds TLV,						
Protective Gloves: Rubber gloves.		Protection: Safety gla		mmended.		
Ventilation Requirements: Adequate ventilation to keep vapor concentration						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable	mediur	m. Incinerate or landfill	according	to local, state	or Federal re	gulations.
Prevent from entering drains or sewers.	o +h	ah narmal use see	dianasal	hazard		
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressur Precautions To Be Taken In Handling & Storage: Do not puncture or incine					30°E	
Other Precautions to be raken in Handling & Storage: Do not puncture of internet Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHIL sources.						ignition
We believe the statements, technical information and recommendations contai	ined her	ein are reliable, but the	y are give	n without warı	anty or guara	ntee of any kind

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only