

Calcium Silicate Corporation, Inc.  
PRODUCT SAFETY INFORMATION

SILI-CAL™ Premium Greens Fertilizer Plus Soil Conditioner  
SILI-CAL™ Macro Grade Fertilizer Plus Soil Conditioner

**I. PHYSICAL AND CHEMICAL PROPERTIES**

Chemical Composition:  $x \text{CaO} \cdot y \text{SiO}_2 \cdot z \text{MgO}$   
Physical State: Solid ( 20° C/ 68°F at 14.7 psia )  
Color: Metallic blue-gray  
Melting Point: 1250°-1500° C /2282°-2732° F  
Bulk Density of Solid: 70-110 LBS./FT<sup>3</sup>  
70 LBS./FT<sup>3</sup> ( Granulated slag - dry )  
75-110 lbs./ft<sup>3</sup> ( granulated slag - wet )  
Solubility: 0.0095 gms at 20° C/68° F. Slightly soluble in hydrochloric acid.

**II. CHEMICAL REACTIVITY**

SILI-CAL™ is relatively inert. It will not chemically react with air or water.

**III. STABILITY**

SILI-CAL™ is stable at ambient temperatures and atmospheric pressure.

**IV. FIRE HAZARD**

SILI-CAL™ is not considered flammable

**V. FIREFIGHTING TECHNIQUE**

None, as this product is not flammable, nor does it create a hazard when involved in a fire.

**VI. TOXICOLOGY**

CAUTION: Dust may create respiratory irritation. AVOID BREATHING DUST.  
Radioactivity: This material contains low concentrations of naturally occurring radio nuclides, including Ra-226 at <5pCi/g. Small quantities of radon and its radioactive decay products will be gradually released with time. These should constitute no significant radiological hazard.

**VII. INDUSTRIAL HYGIENE**

This material is not expected to create any unusual industrial hygiene problems under anticipated use conditions. If handling practices create dust exposure, control of inhalation can be achieved through use of a NIOSH approved dust respirator.

**VIII. STORAGE REQUIREMENTS**

SILI-CAL™ may clump when exposed to moisture. Store in a dry place.

**IX. CORROSIVITY TO MATERIALS OF CONSTRUCTION**

SILI-CAL™ is not corrosive to materials commonly used in construction of process equipment, storage or shipping containers.

**X. DISPOSAL OF UNUSED MATERIAL**

This material should not be used for land-site fill to support public buildings or homes.

**MANUFACTURED BY**  
Calcium Silicate Corporation, Inc.  
P.O. Box 405  
Lake Harbor, Florida 33459  
( 863 ) 902 - 0217